

Projector

Sharp/ NEC P525UL Projector



- No filter service required – a completely sealed optical laser LCD engine allows a filter-free design and brilliant colour brightness is maintained.
- No lamp replacement – up to 20,000 h maintenance free operation possible due to Laser Light Source.
- Professional and Flexible Installation – versatile projection characteristics allow for simple positioning of the projector, making installation easy and potentially saving set up costs.
- Low Noise Level – with 22dB*, the silent technology will not disturb your meeting.
- Risk Group 2 – because of the Risk Group 2 compliance, no prescribed safety precautions are necessary.

Specifications

RESOLUCIÓN DE PANEL

1-Chip DLP(TI) / 3-Chip DLP(TI) / 3-LCD-Panel - / - / •
Resolución Nativa 1920 x 1200 (WUXGA)

TERMINALES VÍDEO

HDMI •

TERMINALES AUDIO

Terminal In/Out RCA-Estéreo •

DATOS IMAGEN

Luminancia ECO-mode (ANSI Lumen) / Standard (ANSI Lumen) 5000 ANSI Lumen (approx. 60% in Eco Mode)
Contraste 500000:1
Fan 22 dB ECO / 24 dB Standard
Lente fija / Lentes Intercambiables - / •
Lente Zoom (Manual/ Motorizada) • / -
Desplazamiento Lente (H/V) • / •
Keystone (manual/auto) • / -

OTROS

Alimentación (V) / Consumo, normal (W) / Consumo, ECO (W) / En Reposo (W) 100 - 240 / 320 / 238 / 0.3
Dimensiones en mm (An x Al x Pr) 480 x 122 x 407
Peso (kg) 9.7

TERMINALES DATA

HDMI •
15 Pin-Sub D (RGB H/V; Y/Ucb/Ucr) •

TERMINALES CONTROL

RS232C (Sub-D) •
LAN •
USB-Host •

ESTÁNDARES DE COLOR

PAL 60/N/M • / • / •
SECAM •
NTSC (MHz) 3.58/ 4.43 • / •

ACCESORIOS

Mando a Distancia / Manual Funcionamiento (CD-ROM) • / •
Cable Alimentación / Cable PC • / -

