

NEC MultiSync® 70GX²Pro



The update of award-winning gaming and lifestyle LCD monitors: 17 inch LCD monitor with "glossy" panel surface, especially designed for the discerning game player and design-conscious home user, with 2 ms (grey-to-grey) response time bringing optimal performance for even the most demanding user.

- Professional LCD monitor with digital TN+ film TFT display
- Slim bezel design
- Stable and excellent picture quality with NTAA (Non-Touch-Auto-Adjustment)
- NaViKey for intuitive monitor setup
- Cable Management

see more.

NEC Display Solutions

[illegible]

Panel Technology	TN+ film TFT
Screen Size [inch/cm]	17 / 43
Pixel Pitch [mm]	0.264
Viewing Angle [°]	160 horizontal / 160 vertical (typ. at contrast ratio 10:1) 176 horizontal / 176 vertical (typ. at contrast ratio 5:1)
Contrast Ratio (typ.)	1000:1
Brightness (typ.) [cd/m²]	400
Response Time (typ.) [ms]	2 (grey-to-grey), 4 (tr - tf)
Colours [Mio.]	16.7
Horizontal Frequency [kHz]	31.5 - 81.1
Vertical Frequency [Hz]	56 - 75
Optimum Resolution	1280 x 1024 at 60 Hz
Supported Resolutions	1280 x 960; 1152 x 870; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 720 x 400; 640 x 480
Connectors	Digital: 1 x DVI-D; Analog: 1 x mini D-sub 15 pin
Plug & Play	VESA DDC/CI; EDID Standard; VESA DDC2B
Adjust Functions	Auto Adjust; Brightness; Colour Temperature Control; Contrast; Fine Adjust (analog); Intelligent Power Management; Language Select; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-Screen-Display (OSD) lock-out; Sharpness; sRGB
Safety and Ergonomics	CE; TCO 03; TÜV Ergonomics; TÜV GS; GEEA/Energy Label; Energy Star; FCC Class B; PCT/Gost; UL/C-UL or CSA; ISO 13406-2 (pixel failure class II); MPRII/MPRIII; RoHS
Power Consumption on Mode [W]	31 (typ.)
Power Consumption Power-Saving Mode [W]	< 2
Power Supply	100-120 V/220-240 V; 1.0 A/0.5 A; internal power supply
Ambient Temperature (operating) [°C]	+5 to +35
Ambient Humidity (operating) [%]	30 to 80
VESA Mounting [mm]	100 x 100
Screen Tilt / Swivel [°]	-5 to +30 / -170 to +170
Dimensions (W x H x D) [mm]	367 x 390.5 x 203
Bezel Width [mm]	13.6
Weight [kg]	5.7
Cable Management	yes
Kensington Lock	yes
OptiClear DVM	yes
Benefits	NaViSet® and NaViSet® Administrator compatible; NTAA (Non-Touch-Auto-Adjustment); OptiClear DVM; Power-Off Timer; Rapid Response Technology; sRGB Support; USB ver. 2.0 (4 down / 1 up)
Audio Functions	None
Colour Versions	Silver Front Bezel, Black Back Cabinet
Shipping Content	Monitor; Power Cable; Signal Cable DVI-D - DVI-D; Signal Cable VGA - VGA; USB Cable; CD-ROM; Sales Office List; User Manual
Warranty	3 years warranty incl. backlight



NEC Display Solutions Europe GmbH