

Projector

Sharp / NEC P603X Projector



- Professional and Flexible Installation – versatile projection characteristics allow for simple positioning of the projector, making installation easy and potentially saving set up costs.
- High brightness – for best performance in bright ambient light.
- Minimized cost of ownership – due to long lamp life and filter exchange intervals.
- Peace of Mind – with future-proof connectivity.
- Cost effective replacement – of existing NEC P model installations to achieve better imaging for lectures and presentations without wall-mount adjustment.

Specifications

RESOLUCIÓN DE PANEL

1-Chip DLP(TI) / 3-Chip DLP(TI) / 3-LCD-Panel	- / - / •
Resolución Nativa	1024 x 768 (XGA)
XGA 1.024 x 768	•

TERMINALES DATA

HDMI	•
15 Pin-Sub D (RGB H/V; Y/Ucb/Ucr)	•

TERMINALES CONTROL

RS232C (Sub-D)	•
----------------	---

ESTÁNDARES DE COLOR

PAL 60/N/M	• / • / •
SECAM	•
NTSC (MHz) 3.58/ 4.43	• / •

ACCESORIOS

Mando a Distancia / Manual Funcionamiento (CD-ROM)	• / •
Cable Alimentación / Cable PC	• / -

ENTRADA PC

H-Frequence (kHz)	15 - 100 KHz
V-Frequence (Hz)	50 - 120 Hz

TERMINALES VÍDEO

S-Video (Y/C)	•
HDMI	•

TERMINALES AUDIO

Mini Jack (3.5 mm) In/Out	•
Terminal In/Out RCA-Estéreo	•
Vía Terminal-HDMI	•

DATOS IMAGEN

Luminancia ECO-mode (ANSI Lumen) / Standard (ANSI Lumen)	3600 / 6000
Contraste	20000:1
Lámpara Proyección (W) / Vida Lámpara ECO-Mode (h) / Vida Lámpara Normal (h)	330 / 8000 / 4000
Fan	34 dB ECO / 37 dB
Lente fija / Lentes Intercambiables	- / •
Lente Zoom (Manual/ Motorizada)	• / -
Desplazamiento Lente (H/V)	• / •
Keystone (manual/auto)	• / -

OTROS

Alimentación (V) / Consumo, normal (W) / Consumo, ECO (W) / En Reposo (W)	100-240 / 414 / 258 / 0.2
Dimensiones en mm (An x Al x Pr)	420 x 133 x 322
Peso (kg)	4.7

