

Monitor sobremesa

SHARP/ NEC MULTISYNC EA271U



NEC MultiSync

- Newest USB Type-C connectivity standard – optimize connectivity and replace video, audio, power and USB cabling with just a single cable to connect your notebook/tablet PC with the display.
- Maximum attention to health and well-being – with outstanding ergonomic height adjustment from 0 to 150 mm; built-in Low Blue Light and Flicker-Free technology; plus integrated ambient light sensor.
- Best in form and function – future-ready design with 3-sided ultra-narrow bezel, available in black or white, complementing a fresh professional office interior.
- Auto-Adjust Power Consumption – to minimize unnecessary power usage, the Human and Ambient Light Sensors adjust the display brightness according to user presence and room lighting conditions.
- Ease of multi-display control – manage the settings of up to 8 displays in a multi-monitor configuration via the master display with ControlSync® technology.

Especificaciones

Tecnología de panel	IPS TFT with W-LED backlight
Relación de aspecto	16:9
Brillo (cd/m2)	350
Relación de contraste	1300:1
[AVSpecificationDynamicContrastRatio]	9000:1
Colores de visualización	1064.64
Tiempo de respuesta (promedio gris a gris) ms	5
Distancia entre píxeles (mm H/V)	0,155
Viewing Angle [°]	178
Características especiales	Ambient light sensor for optimized brightness levels, ControlSync®, Customize Setting, DDC/CI compatible, EcoModes, Frame Comp, ErgoDesign®, Height adjustable stand (150 mm) with 90° Pivot features, Human Sensor, LED Backlight Technology, Picture-by-Picture, Quick release Stand and Handle, Versatile and easy installation (VESA standard) with NaViSet and NaViKey
Eficiencia energética	Ambient light sensor, Carbon Footprint Meter / Carbon Savings Meter, ECOMode, Energy consumption: 22 kWh/1000 h, Energy efficiency class: F, Human sensor, LED backlight technology
Estándares ecológicos	Minimal use of harmful material
Materiales ecológicos	Energy Star 8.0, ErP compatible, RoHS compatible, TCO 8.0
Temperatura de funcionamiento (oC)	5 - 35
Temperatura de almacenamiento [°C]	-10 - 60
Humedad de almacenamiento [%]	10
Humedad de almacenamiento [%]	85
Tamaño diagonal (pulg/cm)	27
Tamaño diagonal (pulg/cm)	68
Gama de colores	110 % sRGB, 81.6% AdobeRGB, 78% NTSC
Digital	DisplayPort, USB Type C (60 W), HDMI, USB ver. 3.1 (3 down / 1 up)
Montaje (VESA/Número de puntos/Inclinación mm)	100 x 100
Bloqueo Kensington	True
Humedad ambiental de funcionamiento (Mín.) [%]	20
Humedad ambiental de funcionamiento (Máx.) [%]	80
Peso del producto con soporte (Kg)	10

Versión de color	Bisel frontal negro, Carcasa trasera negra, Bisel frontal blanco, Carcasa trasera blanca
Gestión de cables	True
Plug & Play	EDID Standard, VESA DDC2Bi, VESA DDCi
Audio	1W + 1W (Desactivable), Toma de auriculares
Funciones de ajuste	Modo DV, Modo Eco, Sensores humanos, Gestión inteligente de la energía, sRGB
Seguridad y ergonomía	CE, EAC, ErP, Flicker-free, ISO 9241-307 (pixel failure class I), Low Blue Light, PSB, RoHS, TÜV Ergonomics, TÜV GS, UL/C-UL or CSA
Garantía limitada del fabricante (años)	3 años de garantía incluida la retroiluminación, 1er a 3er año de garantía opcional para uso ininterrumpido, Ampliación opcional de 4 a 5 años de garantía
Base regulable en altura [mm]	150
Rotación de pantalla [°]	-90 - 90
[AVSpecificationPortraitDimensionsWidthMm]	362
[AVSpecificationPortraitDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsWidthMm]	612
[AVSpecificationLandscapeDimensionsDepthMm]	250
[AVSpecificationPortraitDimensionsHeightMinMm]	629
[AVSpecificationPortraitDimensionsHeightMaxMm]	652
[AVSpecificationLandscapeDimensionsHeightMinMm]	378
[AVSpecificationLandscapeDimensionsHeightMaxMm]	528
Resolución óptima	3840 x 2160 at 60 Hz
Resolución compatible	1024 x 768 , 1280 x 1024, 1152 x 864, 1600 x 1200, 1920 x 1080, 1920 x 1440, 2560 x 1440, 640 x 480, 800 x 600, 832 x 624, 3840 x 2160
Accesorios	
Shipping Content	Control Sync cable, Pantalla, Cable DisplayPort, Cable de alimentación, Manual de instalación, Cable USB
Consumo en modo activado (IEC62087:2012)	150 (max.), 30 (Eco Mode 1), 38 (Eco Mode 2), 38 (shipping)
Alimentación	1.6 A/0.75 A, 100-240 V, Integrated Power Supply
Frecuencia horizontal [kHz]	31.5 - 135
Frecuencia vertical [Hz]	30 - 75
Tamaño del bisel (L/R) mm	1
Tamaño del bisel (U/ mm	1



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp/ NEC MultiSync EA271U, 22/6/2026