Empowered by Innovation NEC

LCDs • Projectors • Plasmas • LCDs • Projectors • Plasmas • LCDs • Projectors

NEC AccuSync® LCD73VM

Entry-level monitors - offering fantastic value for the home and SOHO user.

- Ergonomics and safety complying to the highest industry standards incl. ISO 13406-2
- Rapid Response Technology (5 ms)
- NaViSet® and NaViSet® Administrator compatible
- Versatile installation (VESA standard), with integrated speakers (1+1 W)
- Stable and excellent picture quality with NTAA (Non-Touch-Auto-Adjustment)

see more.

NEC Display Solutions

NEC AccuSync® LCD73VM

TECHNICAL SPECIFICATIONS

Panel Technology	TN+ film TFT
Screen Size [inch/cm]	17 / 43.2
Pixel Pitch [mm]	0.264
Viewing Angle [°]	170 horizontal / 170 vertical (typ. at contrast ratio 5:1) 160 horizontal / 155 vertical (typ. at contrast ratio 10:1)
Contrast Ratio (typ.)	700:1
Brightness (typ.) [cd/m²]	300
Response Time (typ.) [ms]	5 (1.3 white / black; 3.7 black / white)
Colours [Mio.]	16.7
Horizontal Frequency [kHz]	31.5 - 81.1
Vertical Frequency [Hz]	55 - 76
Optimum Resolution	1280 x 1024 at 60 Hz
Supported Resolutions	1280 x 960; 1152 x 870; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 720 x 400; 640 x 480
Connectors	Analog: 1 x mini D-sub 15 pin (captive cable)
Plug & Play	VESA DDC/CI; DDC2B/2Bi; EDID Standard
Adjust Functions	Auto Adjust; Brightness; Colour Temperature Control; Contrast; Fine Adjust (analog); Language Select; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-Screen-Display (OSD) lock-out; Volume
Safety and Ergonomics	CE; TCO 03; TÜV Ergonomics; TÜV GS; Energy Star; FCC Class B; PCT/Gost; UL/C-UL or CSA; CCC; ISO 13406-2 (pixel failure class II); MPR II/ MPR III; RoHS
Power Consumption on Mode [W]	39
Power Consumption Power-Saving Mode [W]	< 2
Power Supply	100-120 V/220-240 V; internal power supply
Ambient Temperature (operating) [°C]	+5 to +35
Ambient Humidity (operating) [%]	30 to 80
VESA Mounting [mm]	100 x 100
Screen Tilt [°]	-5 to +20
Dimensions (W x H x D) [mm]	368 x 382 x 205
Bezel Width [mm]	14.0
Weight [kg]	4.3
Cable Management	yes
Kensington Lock	yes
Benefits	NaViSet®and NaViSet®Administrator compatible; Rapid Response Technology
Audio Functions	Integrated Speakers (1 W + 1 W)
Colour Versions	Silver Front Bezel, Black Back Cabinet
Shipping Content	Monitor; Power Cable; Signal Cable VGA - VGA (captive); Audio Cable; CD-ROM; Sales Office List; User Manual
Warranty	3 years warranty incl. backlight

All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All rights reserved. All specifications are subject to change without notice. 03/09

www.nec-display-solutions.com

NEC Display Solutions Europe GmbH