

Monitor sobremesa

SHARP/ NEC MULTISYNC EA271F



NEC MultiSync

- Ergonomic Office – full height adjustability (150 mm), swivel, tilt and pivot functionality ensures perfect individual ergonomic set-up.
- Protecting your eyes from strain and damage – Built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates any backlight flickering.
- Best in form and function – future-ready design with 3-sided ultra-narrow bezel, available in black or white, complementing a fresh professional office interior.
- Ease of multi-display control – manage the settings of up to 5 displays in a multi-monitor configuration via the master display with ControlSync® technology.
- Maximise image quality with Uniformity Control – benefit from perfect uniformity across multi-screen setups with just one click in the display's on-screen menu.

Especificaciones

Tecnología de panel	AH-IPS LCD with LED backlight
Relación de aspecto	16:9
Brillo (cd/m2)	250
Relación de contraste	1000:1
[AVSpecificationDynamicContrastRatio]	5000:1
Colores de visualización	16.78
Tiempo de respuesta (promedio gris a gris) ms	6
Distancia entre píxeles (mm H/V)	0,311
Eficiencia energética	Ambient light sensor, Auto brightness, Carbon Footprint Meter / Carbon Savings Meter, ECOMode, Energy consumption: 11 kWh/1000 h, Energy efficiency class: C, Human sensor, LED backlight technology
Estándares ecológicos	Efficient mechanical design for minimised packaging, Minimal use of harmful material
Materiales ecológicos	Energy Star 8.0, ErP compatible, TCO 8.0, WEEE
Características especiales	ControlSync®, Carbon Savings Meter, DICOM preset, Customize Setting, DDC/CI compatible, RGB Support, Frame Comp, ErgoDesign®, LED Backlight Technology, Picture-by-Picture, PLink Support, Versatile and easy installation (VESA standard) with NaViSet and NaViKey, Touch Sensor Keys, USB ver. 3.0 (3 down / 1 up), Flicker Free
Resolución óptima	1920 x 1080 at 60 Hz
Resolución compatible	1024 x 768 , 1280 x 1024, 1280 x 960, 1280 x 720, 1440 x 900, 1680 x 1050, 1920 x 1080, 640 x 480, 720 x 400 (70 Hz), 800 x 600
Accesorios	
Shipping Content	Control Sync cable, Cable DisplayPort, Monitor, Cable de alimentación, Manual de instalación, Guía de configuración, Cable USB
Tamaño diagonal (pulg/cm)	27
Tamaño diagonal (pulg/cm)	69
Gama de colores	102 % sRGB, 75.5% AdobeRGB, 72% NTSC
Digital	DisplayPort, DVI-D, HDMI, USB ver. 3.1 (3 down / 1 up)
Analógico	VGA
Montaje (VESA/Número de puntos/Inclinación mm)	100 x 100
Bloqueo Kensington	True

Versión de color	Bisel frontal negro, Carcasa trasera negra, Bisel frontal blanco, Carcasa trasera blanca
Gestión de cables	True
Plug & Play	DDC2B/2Bi, EDID Standard, VESA DDC/CI
Audio	Toma de auriculares, Altavoces integrados (1 W + 1 W)
Funciones de ajuste	Volumen de audio / Bloqueo, Ajuste automático, Brillo, Control de temperatura de color, Contraste, Sincronización de control, Modo DV, Modo Eco, Factory Preset, Fine Adjust (analog), Sensores humanos, Gestión inteligente de la energía, Selección de idioma, Información del monitor, NTAA (Non-Touch-Auto-Adjustment), Bloqueo de pantalla (OSD), Recuperación con un toque, Temporizador de apagado, sRGB
Seguridad y ergonomía	CE, EAC, EnergyStar 8.0, ErP, FCC Class B, Flicker-free, ISO 9241-307 (pixel failure class 2), ISO 9241-307 (pixel failure class I), Low Blue Light, PSB, RoHS, TCO 8.0, TÜV Ergonomics, TÜV GS, UL/C-UL or CSA
Garantía limitada del fabricante (años)	3 años de garantía incluida la retroiluminación, 1er a 3er año de garantía opcional para uso ininterrumpido, Ampliación opcional de 4 a 5 años de garantía
Accesorios opcionales	MDSVSENSOR Value
Base regulable en altura [mm]	150
Giro de pantalla [°]	-170 - Value
Rotación de pantalla [°]	-90 - 90
[AVSpecificationPortraitDimensionsWidthMm]	360
[AVSpecificationPortraitDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsWidthMm]	612
[AVSpecificationLandscapeDimensionsDepthMm]	250
[AVSpecificationPortraitDimensionsHeightMinMm]	628
[AVSpecificationPortraitDimensionsHeightMaxMm]	653
[AVSpecificationLandscapeDimensionsHeightMinMm]	378
[AVSpecificationLandscapeDimensionsHeightMaxMm]	528
Temperatura de funcionamiento (oC)	5 - 35
Temperatura de almacenamiento [°C]	-10 - 60
Humedad de almacenamiento [%]	10
Humedad de almacenamiento [%]	85
Consumo en modo activado (IEC62087:2012)	12 (Eco Mode 2), 17 (Eco Mode), 17 (typ.), 45 (max.)
Alimentación	0.85 A/0.45 A, 100-240 V, Integrated Power Supply
Peso del producto sin soporte (Kg)	5
Peso del producto con soporte (Kg)	8

Frecuencia horizontal [kHz]	31.5 - 83
Frecuencia vertical [Hz]	50 - 75
Tamaño del bisel (L/R) mm	1
Tamaño del bisel (U/ mm	1

Humedad ambiental de funcionamiento (Mín.) [%]	20
Humedad ambiental de funcionamiento (Máx.) [%]	80



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp/ NEC MultiSync EA271F, 23/6/2026