[digital-signage-display]

Sharp MultiSync P556



Purpose-designed for control rooms, passenger information, and prestige retail or corporate signage, the P6 Series delivers uncompromising performance, day after day.

- Enhanced imaging precision – NEC's SpectraView Engine provides full control over colour, gamma, and uniformity for accurate and impactful content.
- Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment.
- Security assured – 802.2x support over LAN enables high-level security for corporate networks, giving peace of mind for IT teams and enterprise environments.
- Mission-critical performance – the P6 series is engineered to deliver lasting clarity and durability in challenging environments without the need for bulky housings.
- Trusted integration – full compatibility with major AV ecosystems, including Crestron XiO Cloud and NVX, Q-Sys, Cisco Webex, Matrox IPMX, and CMS solutions, ensures seamless setup and scalability.

Especificaciones

Tecnología de panel	IPS with Direct LED backlights
Relación de aspecto	16:9
Brillo (cd/m2)	700
Relación de contraste	8000:1
Tiempo de respuesta (promedio gris a gris) ms	8
Distancia entre píxeles (mm H/V)	0,315
Viewing Angle [°]	178
Profundidad de color [bn]	1073 (10bit)
Área activa de la pantalla (H/V) mm	1209.6 x 680.4

Voltaje de funcionamiento (V de CA)/frecuencia (Hz)	100-240
Voltaje de funcionamiento (V de CA)/frecuencia (Hz)	50-60
Consumo (W) (funcionamiento MAX)	115
Temperatura de funcionamiento (oC)	0 to 40
Temperatura de almacenamiento [°C]	-20 to 60
Humedad de almacenamiento [%]	10
Humedad de almacenamiento [%]	80

DisplayPort	1

Nivel de niebla [%]	Pro 25

HDMI	2

Condiciones ambientales

Humedad ambiental de funcionamiento (Mín.) [%]	20
Humedad ambiental de funcionamiento (Máx.) [%]	80

Funciones Adicionales

Garantía limitada del fabricante (años)	3 años de garantía incluida la retroiluminación
Características especiales	DICOM Simulation, CEC Support, HDMI ARC, Scheduler
Certificación de funcionamiento constante	Sí
Atenuación local	Sí
Administración de energía	Sí
Espacio para equipo (montaje)	Sí
Sensor de temperatura	Sí
Sensor de brillo	Sí
Reducción de imagen residual	Sí
Programador/temporizador	Sí
Administración remota	Sí
Control de ganancia	Sí
SNMP	Sí

Peso del producto sin soporte (Kg)	21
Peso de envío (Kg)	27

Horizontal	Sí
Vertical	Sí
Horizontal	Sí
Montaje (VESA/Número de puntos/Inclinación mm)	300 x 300 (FDMI)
Especificación de los tornillos de montaje (tamaño/longitud máx)	M6

Display

Tamaño diagonal (pulg/cm)	54
Tamaño diagonal (pulg/cm)	138

Mecánico

Tamaño del bisel (L/R) mm	11
Tamaño del bisel (U/ mm	11
Tamaño del bisel (L) mm	14

© 2026 Sharp Display Solutions Europe GmbH. All rights reserved. All product names, company names, logos, trademarks, service marks and registered trademarks are the property of their respective owners. Design, features and specifications are subject to change without notice. Information is believed to be accurate at the time of publication. Errors and omissions excepted. Revision date: 09 July 2026. Sharp MultiSync P556, 9/9/2026